



The New Comb Intercom with way, way more... IoT

Introducing the MK II NS (No SIM/GSM), the next generation smart intercom which makes phone calls over the Internet via the Voice Over Internet Protocol (VOIP) and sends TAP codes via the MyComb Mobile app (as the MK II NS has no GSM capabilities). This gives you all the control you are accustomed to, and more in terms of dependencies on cellular network provider failures (downtime due to connectivity).

Ideal for cluster complexes, townhouses, business parks, residential estates and several other access managed environments.

Featuring an entirely new foundation in the form of a redesigned, more robust, and significantly improved PC board.




*Accredited installer recommended for installation



Integrate with Comb Portal

A single comprehensive web based facilities management platform, that integrates with our bespoke hardware and software offerings (*Combware) along with a myriad 3rd party products tailored to suit every access managed eco-system, Comb Portal is undeniably the class leading facility management system. From secure log-in to informative dashboards and the ability to customise to your own requirements. The intuitive navigation allows you to drill down on any queries related to specific hardware with exception based reporting. Pull reports, invite users and update information with ease.



Bright display, even in daylight. The keypad displays clearly, even in dark conditions and offers audible feedback.



Temporary access pins with the integrated Tap-Tap keypad (*Requires the MyComb Mobile application*).



Permanent pin-code for an individual user to provide access.



Gate opening functionality from Centurion Remotes.



Ethernet Port for an Internet connection.



Voice Over Internet Protocol (VOIP).



Gate opening functionality from your mobile with caller-line-identity active.



Pre-defined numbers for reaching emergency services.



Integrate with up to 5 external devices that require a physical connection.



Gate opening functionality from the MyComb mobile application.



Call the intercom to reach security personel.



Allow or deny Access by means of our bespoke Timegrid feature on Comb Portal.



Real-time updates.



Set the timing on incoming and outgoing talk time to avoid misuse.

TECHNICAL SPECIFICATIONS

RELAYS	5
INPUTS	FOR FUTURE USE
INPUT VOLTAGE	9-15v AC/DC
POWER DRAW	15 WATTS
POE COMPLIANT	802.3AT TYPE 2 POE+
USB CONNECTION	YES
SURGE PROTECTION	YES
VOICE OVER INTERNET PROTOCOL	YES
NETWORK CAPABILITY	ETHERNET/WIFI